

off. The gusset forms part of the sleeve, and the pointed end is placed in the lower part of the arm hole and sewed in.

ANOTHER WAY

Another and perhaps better way for family use, is to knit with a fairly heavy yarn and open stitch, a web twice the length required for the body of the shirt. Cut this down one of the stitches from end to end, and fold in the centre; sew up the sides as far as the armholes, and you have a shirt body, cut circular piece for neck, from front, and stitch to back, cut open for breast. Knit arms as before, bind and finish to suit taste.

DRAWERS

Set up as for a man's sock, using cylinder and yarn to suit; knit about six inches of mock rib for the bottom of the leg of the drawers, and knit with a medium stitch, and gradually loosen the stitch until the length of a man's full size hose is knit. Now remove out of the machine in front, 36 needles. The needles lifted out can remain on the inside of the web with their stitches on them, or removed entirely. If the needles are removed, a thread had better be run through the stitches to prevent their raveling out. Now knit flat web straight on the left side and widen out on the right side one stitch about every seven rows until about 144 to 160 rows are knit, and 56 are again in the cylinder. The needles on each side of the flat web will require to be raised, and put down each row of stitches after the widening has caused the yarn and cams to engage with needles of the opposite side of the web. Now knit both sides of the web straight for about 72 to 80 rows, and narrow one stitch on the same side as the widening was done on every seven rows, until about 72 to 80 rows are knit; run off the work; form the second leg in the same manner, only knit the second straight on opposite side and widen and narrow on the opposite side from the first.

Knit two pieces commencing on the 36 needles lifted out of the machine, and gradually widen out in the same manner on one side, and knit straight on the other for about 144 to 160 rows, then knit straight on both sides for about 144 to 160 rows more.

Knit the second piece in the same manner, only widen on the opposite side. A small gusset piece about four inches square will make a better shape to the drawers, if knit and placed in the seat, one corner in each seam of the leg.

The lengths of the various parts, and the narrowings and widenings may be too few or many for some yarns, but practice will enable you to strike the desired sizes.

They should be bound on the top and lined inside of the waist about three or four inches, and a band placed up the front on each side for buttons and button holes.